

X900S GNSS



KEY FEATURES

- **High Precision Static L1/L2 120-channel GNSS Receiver: GPS, GLONASS and BeiDou**
- **Easy to Use - 'Single Button' operation for static operation**
- **Fast Data Download via high speed USB**
- **Compact and Rugged - Integrated rugged design for everyday intensive use**

The CHC X900S dual-frequency GNSS receiver is designed to deliver every surveyor with high precision, robust performances and reliable technology at an affordable price. The X900S GNSS system matches a wide range of applications requiring post-processing static or kinematic survey.

Competitive and Reliable

The X900S breaks the price barrier for centimeter level accuracy positioning and provides extremely quick return on investment compared to equivalent L1/L2 GNSS technology or traditional optical survey equipment.

Outstanding Performances and Easy-of-use

Simply set-up your X900S receiver and switch it on. The GNSS raw data recording starts automatically and will stop when the receiver is powered off. The combination of L1/L2 GNSS technology and advanced post-processing software allows baselines computation up to 100 km.

Compact and Lightweight

The X900S compact design of 179 x 84 mm (7.0 x 3.3 in) with less than 1,4 kg (49 oz) makes the X900S an easy-to-carry GNSS receiver for everyday field work.

Technical Specifications

GNSS characteristics

- 120-channel signal tracking
 - GPS: L1, L2, L2C
 - GLONASS: L1, L2
 - BeiDou: B1
- Multipath mitigation technology
- Optimized for low-elevation satellite tracking

Performance specifications⁽¹⁾

- Post Processing Static
 - Horizontal: 5 mm + 1 ppm RMS
 - Vertical: 10 mm + 1 ppm RMS
- Post-Processed Kinematic (PPK)
 - Horizontal: 5 cm + 1 ppm RMS
 - Vertical: 10 cm + 1 ppm RMS

Communications

- 1x RS232 serial port
- 1x high speed USB
- Integrated Bluetooth® class 2
- Protocols:
 - RINEX and HCN outputs for GNSS raw data
- Data Storage:
 - 4 GB internal memory
 - GPS device mounts as a USB external hard drive

Physical

- Size (HxD): 84 x 179 mm (3.3 x 7.0 in)
- Weight: 1.4 kg with battery (49 oz)
- Operating temperature: -30 °C to + 60 °C (-22 °F to 140 °F)
- Storage temperature: -40 °C to + 70 °C (-40 °F to 158 °F)
- Humidity: 100% condensation
- Waterproof and dust proof: IP67 - protected from temporary immersion to depth of 1 meter, floats
- Shock: survives a 2-meter drop on to concrete

Electrical

- Power consumption: 2.6 W
- Li-ion battery capacity: 2200 mAh
- Operating times on internal battery
 - Up to 6 hours
- External power input: 9-18 VDC

Software (optional)

- Optional CGO software
 - Static office software
 - Combined ease of use and advanced data quality control

(1) Accuracy and reliability specifications may be affected by multi path, satellite geometry and atmospheric conditions. Performances assume minimum of 5 satellites, follow up of recommended survey practices and baseline length < 100 km (static).

Specifications are subject to change without notice.

© 2015 - Shanghai HuaCe Navigation Technology Ltd. All rights reserved. The Bluetooth® world mark and logos are owned by Bluetooth SIG, Inc. The CHC logo and CHC are trademarks of Shanghai HuaCe Navigation Technology Limited. All other trademarks are the property of their respective owners – Rev. January 2015

CHC - Shanghai HuaCe Navigation Technology Ltd.
599 Gaojing Road, Building C
201702 Shanghai, China

Tel : +86 21 542 60 273
Fax : +86 21 649 50 963

Email : sales@chcnv.com | www.chcnv.com